



BalancePro

PEDESTAL LINE





A complete range From 25 to 1025 mm



all in 1
system



TBP4



TR-BP



TX-BP



TD-BP

Also available in 2
and 3mm thickness

TILE

DECKING



BPX14



BPR13



BPD11



BP412

The raised floor from a new point of view

SELF-LEVELLING OR FIXED
REGULATION FROM THE TOP
LOAD CAPACITY UP TO 1.000 KG
GREAT EXCURSION ALL IN ONE
AVAILABLE SELF-EXTINGUISHING

SELF-LEVELLING HEAD
AUTOMATIC CORRECTION

up to 5%

AND UP TO 10% WITH THE SLOPE CORRECTORS EASY FLAT

TOPKEY

With the regulation key you can easily and quickly regulate the supports from the top.

TWIST LOCK RING

Once you set the lock ring in the support, you can regulate it laterally from the base (even if you have placed it in the centre of a tile). Useful in the absence of TopKey.

ANTISHOCK

Interchangeable rubber shim.

FIX RING

With the Fix Ring you can block the tilt movement to obtain a support with fixed head and further improve the stability of the flooring, for example when you have to install a small tile on the edge of the terrace.

THREADED SCREW

The strong screw thread allows to reach capacities up to 1.000 kg, guaranteeing great excursions and quick installation.

EXTENSION

The use of the extensions allows the excursion of the supports to be increased by 10 cm, simplifying the logistic management and consequent reduction of the warehouse stock and faster supplies.

BALANCE PRO

The tilt movement of Balance Pro is the hearth of our new system that allows to automatically correct the slope up to 5%. The particular concave shape of the head, once the correction position is reached, lays on the convex part of the screw.

The design is the evolution of Balance system which has always been appreciated for its installation speed and walking stability.

BASE

The support base, with its generous diameter, allows the weight of the entire flooring to be distributed over a large surface.



W W W . I M P E R T E K . C O M



IMPERTEK Srl
via Po 507 · 30022 · Ceggia Venezia · Italy
T+39 0421 322 525 r.a. · F+39 0421 322 756
info@impertek.com · www.impertek.com

